



Titel:	Abt.		Datei Nr.:
Verladerichtlinien	Verladung		001

Loading guidelines

- Collection address:

Artur Naumann Stahl AG
Bataverstr. 90
41642 Neuss, Germany

- Loading times:

Monday – Thursday from 07:00 – 15:00,
Friday from 07:00 – 13:00

- Notes

Trucks are loaded using either a magnet crane or a forklift, depending on the dimensions and weight of the load.

The **maximum total permissible weight (truck + load) is 40 tonnes.**

For **insurance reasons**, we cannot unload third-party materials.

We cannot load materials on top of pipes or profiles.

Check the dimensions of the material to be collected carefully! This information can be found in the documents provided.

Box-body vehicles and vans can only be loaded if the vehicle is equipped with the **appropriate lashing points in accordance with DIN EN 12 640.-**

Titel:	Abt.	Datei Nr.:
Verladerichtlinien	Verladung	001

- Required loading equipment:



Helmet



Safety boots



Anti-slip mats



Lashing belts in accordance with DIN EN 12195-2

or



Chains in accordance with DIN EN 12195-3

For maximum loading widths, see the example images below



Tautliner
Maximum width 2400 mm



Tautliner, adjustable width Maximum width 3000 mm



Titel:	Abt.	File Nr.:
Verladerichtlinien	Verladung	001

- Further examples:



Flatbed truck
Maximum width 3000 mm



Oblique loader
Maximum width 4200 mm
Loaded in horizontal position only



Titel:	Abt.		Datei Nr.:
Verladerichtlinien	Verladung		001

- Instructions for deliveries and collections:

Health and safety are a top priority for our company, so we ensure that safety regulations are followed at all times, including during vehicle loading!

We will only load vehicles that satisfy the following conditions:

- o The vehicle must be appropriate for the load type (in line with requirements set out in VDI 2700). The vehicle must be capable of holding the load securely in a form-fitting manner, both in the direction of travel and to the sides.
- o The vehicle must be equipped with lashing points in accordance with DIN EN 12 640 .
- o The vehicle must carry lashing belts in accordance with DIN EN 12 195-2 or chains in accordance with DIN EN 12 195-3.
- o The vehicle driver must wear appropriate protective clothing (safety helmet in accordance with DIN EN 397 and S3 safety boots in accordance with EN 20 345 or EN 345-1.
- o The driver is required to follow the instructions of our loading team at all times and to comply with the safety regulations.
Vehicles that do not satisfy the requirements or that are not fitted with the necessary equipment will not be loaded!

If the material is being collected from us by a freight company, please pass on this information to the company or ask the company to refer to our website www.naumann-stahl.de to check the requirements.